

Platform

0.75 m x 1.01 m (W x L) Slide bar rear entry aluminium platform

Safety interlocked controls

Full proportional drive joystick control with integral thumb steer switch

Lanyard attachment anchor

Power & Transmission

4 x 6 Volt, 180 A/Hr deep cycle batteries

Automatic dual voltage high frequency battery charger

Battery condition indicator on platform

Direct electric two wheel drive

Brushless AC drive motors

Brake release

Functional Equipment & Accessories

Low maintenance non-rotating extruded aluminium mast

Passive pothole protection system

Non marking solid rubber tyres

0.78 m wide frame

Manual Descent

2 degree Tilt indicator and alarm

Key lock main power switch

Hour meter

Transportation tie-down points

Lifting eye for crane hook

Fork truck lift points

Horn

Descent alarm

Available Options

AC power cable to platform

4 x 6 Volt, 180 A/Hr gel batteries

Battery discharge indicator with low charge function cut-out

Xenon strobe lights

Tool tray (0.12 m x 0.36 m x 0.10 m)

Fluorescent tube caddy

Food compatible lubrication and hydraulic oil

Low temperature lubrication

JLG Industries Inc.

Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands

Tel: +31 (0)23 565 5665

Fax: +31 (0)23 557 2493

e-mail address: europa@jlg.com

www.jlgeurope.com

An Oshkosh Corporation Company

Printed in UK
FORM No.: DS101-0208-500
PART NO.: DS101-ENGLISH



Toucan Junior 6

Working height	6.00 m
Platform height	4.00 m
Platform capacity	200 kg ²
Elevating Shelf capacity	—
A1. Platform size (W x L)	0.75 m x 1.01 m
A2. Elevating shelf size (W x L)	—
B. Overall width	0.78 m
C. Stowed height	1.79 m
D. Overall length	1.50 m
E. Wheelbase	1.20 m
F. Ground clearance	8 cm
Chassis width	0.78 m
Machine weight *	850 kg
Maximum ground bearing pressure	13.20 kg/cm ²
Drive speed - lowered	4 km/h
Drive speed - elevated	1 km/h
Turning radius (outside)	1.51 m
Turning radius (inside)	0.00 m
Gradeability	20%
Distance from platform to wall (standard platform) – over front	0.00 m
Distance from platform to wall (standard platform) – over sides	0.00 m
Tyres (non-marking solid)	300 x 80
Electrical system	24V DC
Batteries	24V – 180 A/hr
Dual Voltage 110/240V Charger	24V – 15A
Drive motors	2 motors 24V AC - 320 W
Brakes	Electromagnetic
Electrical motor	1 kW
Hydraulic system	6 L

¹ Capacities shown are for 1 person indoors only

² Capacities shown are for 2 persons indoors only

*Certain options or country standards may increase weight and/or dimensions.

